

Printing date 28.03.2017

Safety data sheet according to 1907/2006/EC, Article 31

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: Aerosol NC · Article number (product ID.): REZ04 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Application of the substance / the mixture: painting · Uses advised against No further relevant information available. · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Peter Kwasny GmbH Heilbronner Str. 96 D-74831 Gundelsheim Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de · Further information obtainable from: Product safety department · 1.4 Emergency telephone number: Tel.:+49 6269 95 20 · national: National Poisons Information Service, Birmingham Tel.: 844 892 0111 · K-Nr. 0001 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1 GHS07 Causes serious eye irritation.

Eye Irrit. 2 H319Causes serious eye irritation.STOT SE 3 H336May cause drowsiness or dizziness.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

• *Hazard-determining components of labelling:* acetone n-butyl acetate Page 1/10

Revision: 28.03.2017

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol NC

	(Contd. of page 1)
• Hazard sta	itements
H222-H22	9 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
· Precaution	nary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P305+P35	51+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P31	<i>If eye irritation persists: Get medical advice/attention.</i>
P410+P41	2 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional	information: Without adequate ventilation, explosive atmosphere/gas mix may be created.
· 2.3 Other	hazards
· Results of	PBT and vPvB assessment
· PBT: Not	
D D 17	

· **vPvB:** Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2	acetone	25-<50%
Reg.nr.: 01-2119471330-49-xxxx		
CAS: 106-97-8	butane (containing $\leq 0,1$ % butadiene (203-450-8))	10-<25%
EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	🚸 Flam. Gas 1, H220; 🔗 Press. Gas C, H280	
CAS: 74-98-6	propane	10-<25%
EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	🚸 Flam. Gas 1, H220; 🔗 Press. Gas C, H280	
CAS: 123-86-4	n-butyl acetate	5-<10%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	🚸 Flam. Liq. 3, H226; 솻 STOT SE 3, H336	
CAS: 1330-20-7	xylene	5-<10%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	🚸 Flam. Liq. 3, H226; 🕕 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 9004-70-0	Nitrocellulose	5-<10%
	🚸 Flam. Sol. 1, H228	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	2.5-<5%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226	
Reg.nr.: 01-2119475791-29-xxxx		
	(Con	td. on page 3)

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol NC

	(Co	ntd. of page 2)
CAS: 64-17-5	ethanol	2.5-<5%
EINECS: 200-578-6	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319	
CAS: 108-10-1	4-methylpentan-2-one	2.5-<5%
EINECS: 203-550-1	(Flam. Liq. 2, H225; (Acute Tox. 4, H332; Eye Irrit. 2,	1
Reg.nr.: 01-2119473980-30-xxxx		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Cool container whit water

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
 Do not flush with water or aqueous cleansing agents
 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Take note of emission threshold.

(Contd. on page 4)

GB

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol NC

(Contd. of page 3)

Use only in well ventilated areas. Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

 Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• *Requirements to be met by storerooms and receptacles:* Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workpl 67-64-1 acetone	
WEL Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm	
106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))	
WEL Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	
123-86-4 n-butyl acetate	
WEL Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm	
1330-20-7 xylene	
WEL Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV	
108-65-6 2-methoxy-1-methylethyl acetate	
WEL Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk	
64-17-5 ethanol	
WEL Long-term value: 1920 mg/m³, 1000 ppm	
108-10-1 4-methylpentan-2-one	
WEL Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk, BMGV	
	(Contd. on page

Safety data sheet ticle 31

according to 1907/2006/EC, Article 31			
inting da	e 28.03.2017		Revision: 28.03.201
ade nam	e: Aerosol NC		
			(Contd. of page
· Ingredi	ents with biological lim	t values:	
)-7 xylene		
BMGV	650 mmol/mol creatinin Medium: urine Sampling time: post shi Parameter: methyl hipp	Ì	
108-10-	1 4-methylpentan-2-on		
BMGV	20 µmol/L Medium: urine Sampling time: post shi Parameter: 4-methylper	it atan-2-one	
· Additio	nal information: The lis	ts valid during the making were used as basis.	
 General Keep av Immedi Wash h Do not Avoid of Avoid of Respiral Respiral Respiral Protect The glo Selecti degrada Materia Gloves The exa observe For the suitable 	ands before breaks and a inhale gases / fumes / ae ontact with the eyes. ontact with the eyes and tory protection: workers are facing con fors. Half mask with com- tors. Half mask with com- tor of hands: we material has to be im- on of the glove materiation at of gloves Nitrile rubbe- tion time of glove materiation at the changed after ev- to break trough time had d. e permanent contact of the contact of the contact of the contact of the contact of the contact of the contact of the contact of t	rages and feed. nd contaminated clothing it the end of work. rosols. skin. centrations above the exposure limit they must use bination filter, class A1P2 minimum, or breathing mas bermeable and resistant to the product/ the substance/ al on consideration of the penetration times, rate r, NBR ial very contamination. s to be found out by the manufacturer of the protecti c a maximum of 15 minutes gloves made of the fe	sk with outer air supply the preparation. es of diffusion and th ive gloves and has to b
	Tignity sected 50580		
SECT	ION 9: Physical and	chemical properties	
• 9.1 Infe	ormation on basic physic	al and chemical properties	
· Genera	l Information		
· Appear		Aarosol	
Form Coloi		Aerosol According to product specification	
· Odour:		<i>Characteristic</i>	
· Odour	hreshold	Not determined	

Not determined.

· Odour threshold:

(Contd. on page 6) GB

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol NC

	(Contd. of page
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	n: Not applicable, as aerosol.
Flash point:	<0 °C
	Without propellant gas.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	365 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	13.0 Vol %
Vapour pressure at 20 °C:	3600 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	82.7 %
	With propellant gas. Content given by weight.
VOC (EU)	82.66 %
Solids content:	17.3 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- \cdot 10.6 Hazardous decomposition products: Possible in traces.

(Contd. on page 7)

GB

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol NC

(Contd. of page 6)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

	· LD/LC50 values relevant for classification: 1330-20-7 xylene		
	Oral	LD50	4300 mg/kg (rat)
	Dermal	LD50	2000 mg/kg (rabbit)
	Inhalative	LC50/4 h	21.7 mg/l (rat)

• Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

1330-20-7 xylene

LC50/96h 1570 µg/l (Cyprinus carpio)

Median

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

(Contd. on page 8)

GB -

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol NC

(Contd. of page 7)

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

1 A 1 TINI Normal and	
14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
	not classified
14.5 Environmental hazards:	N
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	not classified F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clea of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacit above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Ann. Marpol and the IBC Code	ex II of Not applicable.
	(Contd. on page

Printing date 28.03.2017

Revision: 28.03.2017

Trade	name: Aerosol NC	

		(Contd. of page 8
· Transport/Additional information:		
ADR		
· Limited quantities (LQ)	1L	
Excepted quantities $(\widetilde{E}Q)$	Code: E0	
	Not permitted as Excepted Quantity	
Transport category	2	
Tunnel restriction code	D	
IMDG		
Limited quantities (LQ)	1L	
Excepted quantities $(\widetilde{E}Q)$	Code: E0	
· · ~	Not permitted as Excepted Quantity	
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	50-100

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H228 Flammable solid.
H280 Contains gas under pressure; may explode if heated.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product safety department
- · Contact: Hr. Hamberger

(Contd. on page 10)

[—] GB

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol NC

(Contd. of page 9) · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas C: Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Flam. Sol. 1: Flammable solids – Category 1 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 • * Data compared to the previous version altered.