



Printing date 24.01.2019 Version number 1.03 Revision: 24.01.2019

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Graffity remover

· Article number: 75672

· UFI: 0G21-J0Y0-1001-TV6V

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Material for hobby and creative art

· Details of the supplier of the safety data sheet

Manufacturer/Supplier: CREARTEC trend-design-gmbh Lauenbühlstr. 59 D-88161 LINDENBERG DEUTSCHLAND

Further information obtainable from:

Abteilung Produktsicherheit

info@creartec.info

Emergency telephone number:

During opening hours: +49 8381 80740-0

Mon -Thu from 08.30 to 16.30 and Fri from 08.30 to 12.30

Emergency calls: +49 151 44613864 (24h)

2 Hazards identification

- · Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

0...0.

- · Signal word Warning
- · Hazard-determining components of labelling:

1-methoxy-2-propanol

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

(Contd. on page 2)

Printing date 24.01.2019 Version number 1.03 Revision: 24.01.2019

Trade name: Graffity remover

(Contd. of page 1)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Labelling of packages where the contents do not exceed 125 ml
- · Hazard pictograms





· Signal word Warning

· Hazard-determining components of labelling:

1-methoxy-2-propanol

Hazard statements

H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	· · · · · · · · · · / = · · · · · · · · · · · · · · · · ·	> 50 – ≤ 100%
EINECS: 203-539-1	🚸 Flam. Liq. 3, H226; 🕂 STOT SE 3, H336	
		> 2.5 – ≤ 10%
EINECS: 205-500-4	🏇 Flam. Liq. 2, H225; 💠 Eye Irrit. 2, H319; STOT SE 3, H336	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)

Printing date 24.01.2019 Version number 1.03 Revision: 24.01.2019

Trade name: Graffity remover

· Additional information Cool endangered receptacles with water spray.

(Contd. of page 2)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

Sk

141-78-6 ethyl acetate

WEL | Short-term value: 1468 mg/m³, 400 ppm

Long-term value: 734 mg/m³, 200 ppm

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

(Contd. on page 4)

Printing date 24.01.2019 Version number 1.03 Revision: 24.01.2019

Trade name: Graffity remover

(Contd. of page 3)

· Protection of hands:

Check protective gloves prior to each use for their proper condition.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: Colourless
Odour: Ester-like
Odour threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/freezing point: -96.7 °C Initial boiling point and boiling range: 120 °C · Flash point: 31 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 270 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures

are possible.

· Explosion limits:

Lower:
Upper:

Vapour pressure at 20 °C:

Density at 20 °C:

Relative density

Vapour density

Evaporation rate

2.3 Vol %

~ 20 Vol %

12 hPa

0.91 g/cm³

Not determined.

Not determined.

· Solubility in / Miscibility with

water: 99.44 g/L

· Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 5)

Printing date 24.01.2019 Version number 1.03 Revision: 24.01.2019

Trade name: Graffity remover

(Contd. of page 4)

· Viscosity:

Dynamic at 20 °C: 1.72 mPas
Kinematic: Not determined.

· Solvent content:

Organic solvents: 100.0 %
Solids content: 0.0 %

Other information
 No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions Reacts with strong oxidising agents.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

	7 =, which is a second of the second			
· LD/LC50 values relevant for classification:				
107-98-2 1-methoxy-2-propanol				
Oral	LD50	5,660 mg/kg bw (rat)		
Dermal	LD50	13,000 mg/kg bw (rabbit)		
141-78-6	141-78-6 ethyl acetate			
Oral	LD50	5,620 mg/kg bw (rabbit)		
Inhalative	LC50/4 h	1,600 mg/l (rat)		

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability Easily biodegradable
- · Behaviour in environmental systems:
- · Bioaccumulative potential

Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.

- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 6)

Printing date 24.01.2019 Version number 1.03 Revision: 24.01.2019

Trade name: Graffity remover

(Contd. of page 5)

Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
07 01 04*	other organic solvents, washing liquids and mother liquors	
HP 3	Flammable	
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

· UN-Number

· IMDG, IATA

- · ADR, IMDG, IATA
- · UN proper shipping name
- · ADR

1993 FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol,

ETHYL ACETATE) FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol, ETHYL

ACETATE)

UN1993

· Transport hazard class(es)

· ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label

· Packing group

· ADR, IMDG, IATA Ш

Not applicable. · Environmental hazards:

· Special precautions for user Warning: Flammable liquids.

· Danger code (Kemler): 30 · EMS Number: F-E,<u>S-E</u> Stowage Category

Transport in bulk according to Annex II of Marpol and

the IBC Code Not applicable.

· Transport/Additional information:

· Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· Transport category

D/E · Tunnel restriction code

· IMDG

· Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN 1993 FLAMMÁBLE LIQUID, N.Ö.S. (1-METHOXY-2-· UN "Model Regulation":

PROPANOL, ETHYL ACETATE), 3, III

GB -

Printing date 24.01.2019 Version number 1.03 Revision: 24.01.2019

Trade name: Graffity remover

(Contd. of page 6)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Abteilung Produktsicherheit
- Contact: Dr. B. Gangnus
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB