Trade name: MOLOTOW™ Permanent Paint

Current version: 2.0.1, issued: 09.11.2016 Replaced version: 2.0.0, issued: 07.09.2016 Region: GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name

MOLOTOW™ Permanent Paint, 420.000, 440.000, 620.000, 640.000, 862.001, 862.002, 862.003, 862.004, 862.005, 862.006; 862.101, 862.102, 862.103, 862.104, 862.105, 862.106, 862.107, 862.108

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses of the substance or mixture

writing and marking

#### Uses advised against

No data available.

#### 1.3 Details of the supplier of the safety data sheet

#### Address

Feuerstein GmbH - MOLOTOW™ Distribution Willy-Brandt-Straße 9/2

D-77933 Lahr / Schwarzwald

Phone: +49 (0) 7821 92229 0 [8:00 - 17:00 (UTC+1)]

## Information provided by / telephone

Chemisches Labor

Phone: +49 (0) 7821 92229 0 [8:00 - 17:00 (UTC+1)]

Fax.: +49 (0)721 92 229 99

## Advice on Safety Data Sheet

info@molotow.com

## 1.4 Emergency telephone number

For medical advice (in German and English):

Phone: +49 (0) 7821 92229 0 [8:00 - 17:00 (UTC+1)]

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 STOT SE 3; H336

#### Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC)  $n^{\circ}$  1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

## 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

#### Hazard pictograms





Signal word Warning

Trade name: MOLOTOW™ Permanent Paint

Current version: 2.0.1, issued: 09.11.2016 Reglaced version: 2.0.0, issued: 07.09.2016 Region: GB

## Hazardous component(s) to be indicated on label:

1-methoxy-2-propanol

**Hazard statements** 

H226 Flammable liquid and vapour.H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.

#### 2.3 Other hazards

No data available.

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not applicable. The product is not a substance.

#### 3.2 Mixtures

### Chemical characterization

Mixture based on: alcohols; Resins; Pigments; dyes

Hazardous ingredients

No	Substance name		Additional information				
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Cond	centration		%	
1	1-methoxy-2-propanol						
	107-98-2 203-539-1 603-064-00-3	Flam. Liq. 3; H226 STOT SE 3; H336	>=	25.00 - <	85.00	%-b.w.	
2		1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[N-(4 chloro- nyl)-3-oxobutyramide]		, ,			
	5567-15-7 226-939-8 -	Aquatic Chronic 3; H412	<	2.50	,	%-b.w.	
3	Amines, C12-18-all	kyldimethyl	1 "				
	68391-04-8 269-923-6 -	Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Skin Corr. 1B; H314	<	0.10		%-b.w.	
4	titanium-dioxide						
	13463-67-7 236-675-5 -		>=	0.00 - <	30.00	%-b.w.	

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
3	-		M = 100	M = 1

## 3.3 Other information

Concentration data refers to the individual colors.

Trade name: MOLOTOW™ Permanent Paint

Current version: 2.0.1, issued: 09.11.2016 Replaced version: 2.0.0, issued: 07.09.2016 Region: GB

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

#### **General information**

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes and launder thoroughly before reusing.

#### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

#### After skin contact

When in contact with the skin, clean with soap and water.

### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

#### After ingestion

Rinse mouth thoroughly with water. Call a doctor. Do not induce vomiting. Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

## 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

## Suitable extinguishing media

Extinguishing powder; Foam; Carbon dioxide; Water mist

#### Unsuitable extinguishing media

High power water jet

## 5.2 Special hazards arising from the substance or mixture

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide and smoke.

### 5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

## For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Do not inhale vapours. Keep away sources of ignition.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

#### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

## 6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Send in suitable containers for recovery or disposal.

## 6.4 Reference to other sections

No data available.

Trade name: MOLOTOW™ Permanent Paint

Current version: 2.0.1, issued: 09.11.2016 Replaced version: 2.0.0, issued: 07.09.2016 Region: GB

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

#### Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn.

### General protective and hygiene measures

Keep away from foodstuffs and beverages. Do not eat, drink or smoke during work time. Wash hands before breaks and after work. Remove soiled or soaked clothing immediately. Wash soiled clothing. Do not inhale vapours. Avoid contact with eyes and skin. Provide eye wash fountain in work area. Have emergency shower available. Use barrier skin cream.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - refrain from smoking. Vapours can form an explosive mixture with air. Take precautionary measures against static charges.

### 7.2 Conditions for safe storage, including any incompatibilities

## Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect of heat.

#### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

#### Advice on storage assembly

Do not store together with: Oxidizing agents

## 7.3 Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

## Occupational exposure limit values

No	Substance name	CAS no.		EC no.					
1	1-methoxy-2-propanol	107-98-2		203-539-1					
	2000/39/EWG								
	1-Methoxypropanol-2								
	STEL	568	mg/m³	150	ml/m³				
	TWA	375	mg/m³	100	ml/m³				
	Skin resorption / sensibilisation	Skin	0S	- 22	112				
	List of approved workplace exposure lim	its (WELs) / EH40							
	1-Methoxypropan-2-ol	75			_				
	STEL	560	mg/m³	150	ml/m³				
	TWA	375	mg/m³	100	ml/m³				
	Skin resorption / sensibilisation	Sk	200 - O		714				
2	titanium-dioxide	13463-67-7		236-675-5					
	List of approved workplace exposure limits (WELs) / EH40								
	Titanium dioxide								
	total inhalable dust								
	TWA	10	mg/m³						
	List of approved workplace exposure limits (WELs) / EH40								
	Titanium dioxide								
	respirable dust								
	TWA	4	mg/m³						

Trade name: MOLOTOW™ Permanent Paint

Current version: 2.0.1, issued: 09.11.2016 Replaced version: 2.0.0, issued: 07.09.2016 Region: GB

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

#### Personal protective equipment

### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Respiratory filter (gas):

### Eye / face protection

Safety glasses (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material butyl rubber

Material thickness 0.5 mm Breakthrough time > 8 h

#### **Environmental exposure controls**

No data available.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Form/Colour				
liquid				
product specific				
Odour				
ethereal				
Odour threshold				
No data available				
pH value				
Not applicable				
Boiling point / boiling range				
Value	аррг.	120	°C	
Melting point / melting range				
No data available				
Decomposition point / decomposi	ition range			
No data available				
Flash point	S	50	701	
Value		31	°C	
Method	DIN EN 456			
Ignition temperature			Ar.	
Value	>	250	°C	
Source	Literature value			

Trade name: MOLOTOW™ Permanent Paint

Current version: 2.0.1, issued: 09.11.2016 Reglaced version: 2.0.0, issued: 07.09.2016 Region: GB

Auto-ignition temperature				
No data available				
Oxidising properties				
No data available				
Explosive properties				
No data available				
Flammability (solid, gas)				
No data available				
Lower flammability or explosive limits			0	
Value		1.7	% vol	
Upper flammability or explosive limits				
Value Source	Literature value	11.5	% vol	
	Literature value			
Vapour pressure Value		12	mbar	
Reference temperature		20	°C	
Vapour density	1 20 10			
No data available				
Evaporation rate				
No data available				
Relative density				
No data available				
Density	4 2	-		
Value	0.9 -	1.3	g/cm³	
Reference temperature		20	°C	
Solubility in water	n antially male albia			
Remarks	partially miscible			
Solubility(ies)				
No data available				
Partition coefficient: n-octanol/water  No data available				
Viscosity Value	appr.	30	sec	
Method	DIN cup 3 mm	00	300	
Solvent content				
Value	<	82	%	
ale de la company de la compan	n6 e3 62		-10	

## 9.2 Other information

Other information	
No data available.	

## SECTION 10: Stability and reactivity

## 10.1 Reactivity

No data available.

## 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

Trade name: MOLOTOW™ Permanent Paint

Current version: 2.0.1, issued: 09.11.2016 Replaced version: 2.0.0, issued: 07.09.2016 Region: GB

## 10.3 Possibility of hazardous reactions

None, if handled according to order.

### 10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

### 10.5 Incompatible materials

strong oxidizing agents

## 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

Acute oral toxicity	

No data available

#### Acute dermal toxicity

No data available

#### Acute inhalational toxicity

No data available

#### Skin corrosion/irritation

No data available

## Serious eye damage/irritation

No data available

### Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

## Reproduction toxicity

No data available

#### Carcinogenicity

No data available

## STOT-single exposure

No data available

## STOT-repeated exposure

No data available

#### Aspiration hazard

No data available

## Symptoms related to the physical, chemical and toxicological characteristics

The product can cause skin and eye irritation.

Trade name: MOLOTOW™ Permanent Paint

Current version: 2.0.1, issued: 09.11.2016 Replaced version: 2.0.0, issued: 07.09.2016 Region: GB

## **SECTION 12: Ecological information**

## 12.1 Toxicity

## Toxicity to fish (acute)

No data available

#### Toxicity to fish (chronic)

No data available

## Toxicity to Daphnia (acute)

No data available

### Toxicity to Daphnia (chronic)

No data available

#### Toxicity to algae (acute)

No data available

#### Toxicity to algae (chronic)

No data available

### **Bacteria** toxicity

No data available

### 12.2 Persistence and degradability

No data available.

## 12.3 Bioaccumulative potential

No data available.

## 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

No data available.

## 12.6 Other adverse effects

No data available.

## 12.7 Other information

#### Other information

Do not discharge product unmonitored into the environment.

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Smaller quantities can be disposed with household garbage.

## Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

Trade name: MOLOTOW™ Permanent Paint

Current version: 2.0.1, issued: 09.11.2016 Replaced version: 2.0.0, issued: 07.09.2016 Region: GB

## **SECTION 14: Transport information**

## 14.1 Transport ADR/RID/ADN

Class F1 Classification code Packing group Ш Hazard identification no. 30 UN number UN1263 Technical name PAINT Special Provision 640 640E Tunnel restriction code D/E Label 3

#### 14.2 Transport IMDG

Class 3 Packing group III UN number UN1263 Proper shipping name PAINT F-E+S-E EmS Label 3

### 14.3 Transport ICAO-TI / IATA

Class 3 Packing group 111 UN number UN1263 Proper shipping name Paint Label 3

## 14.4 Other information

No data available.

## 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

## 14.6 Special precautions for user

No data available.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

## Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

### REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

### Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe No 3, 40 XVII.

## Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:

Trade name: MOLOTOW™ Permanent Paint

Current version: 2.0.1, issued: 09.11.2016 Replaced version: 2.0.0, issued: 07.09.2016 Region: GB

Directive 1999/13/EC on the limitation of emissions of volatile organic compounds due to the use of organic solvents (VOC Directive)

VOC content < 82 %

Other regulations

Adhere to the national sanitary and occupational safety regulations when using this product.

#### 15.2 Chemical safety assessment

For this mixture a chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

#### **Further information**

Use restriction recommended by the manufacturer:

In large drums ink is for professional use only.

#### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

# Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

## Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO Umwelt Consult GmbH.