



UV resistant varnish satin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Date of issue: 21-02-2014

Revision date:

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : UV resistant varnish satin
Product code : 981

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Varnish

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Old Holland Classic Colours Since 1664
Nijendal 36
3972 KC Driebergen Rijsenburg - Nederland
T 0031 343 518 224 - F 0031 343 516 342
info@oldholland.com - www.oldholland.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Skin Sens. 1 H317
STOT SE 3 H336
Asp. Tox. 1 H304
Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

F; R11
Xn; R65
R43
N; R51/53
R66
R67

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02



GHS07



GHS08



GHS09

UV resistant varnish satin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Signal word (CLP)	: Danger
Hazardous ingredients	: reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionylpoly(oxyethylene)
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour H304 - May be fatal if swallowed and enters airways H317 - May cause an allergic skin reaction H336 - May cause drowsiness or dizziness H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P261 - Avoid breathing vapours, mist, spray P273 - Avoid release to the environment P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, doctor P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P331 - Do NOT induce vomiting
EUH phrases	: EUH066 - Repeated exposure may cause skin dryness or cracking

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)	(EC no) 919-446-0 (REACH-no) 01-2119458049-33	< 75	Xn; R65 N; R51/53 R10 R66 R67
Solventnaphta 170	(CAS No) 64742-95-6 (EC no) 918-668-5 (REACH-no) 01-2119455851-35	10 - 25	Xn; R65 Xi; R37 N; R51/53 R10 R66 R67
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionylpoly(oxyethylene)	(EC no) 400-830-7 (EC index no) 607-176-00-3 (REACH-no) 01-0000015075-76	1 - 5	R43 N; R51/53
SILICA	(CAS No) 7631-86-9 (EC no) 231-545-4	1 - 5	Not classified
methanol	(CAS No) 67-56-1 (EC no) 200-659-6 (EC index no) 603-001-00-X	< 1	F; R11 T; R23/24/25 T; R39/23/24/25

Name	Product identifier	Specific concentration limits
methanol	(CAS No) 67-56-1 (EC no) 200-659-6 (EC index no) 603-001-00-X	(3 =< C < 20) Xn;R20/21/22 (3 =< C < 10) Xn;R68/20/21/22 (10 =< C) T;R39/23/24/25 (20 =< C) T;R23/24/25

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)	(EC no) 919-446-0 (REACH-no) 01-2119458049-33	< 75	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Solventnaphta 170	(CAS No) 64742-95-6 (EC no) 918-668-5 (REACH-no) 01-2119455851-35	10 - 25	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

UV resistant varnish satin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	(EC no) 400-830-7 (EC index no) 607-176-00-3 (REACH-no) 01-0000015075-76	1 - 5	Skin Sens. 1, H317 Aquatic Chronic 2, H411
SILICA	(CAS No) 7631-86-9 (EC no) 231-545-4	1 - 5	Acute Tox. 2 (Inhalation:dust,mist), H330
methanol	(CAS No) 67-56-1 (EC no) 200-659-6 (EC index no) 603-001-00-X	< 1	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT SE 1, H370
Name	Product identifier	Specific concentration limits	
methanol	(CAS No) 67-56-1 (EC no) 200-659-6 (EC index no) 603-001-00-X	(3 =< C < 10) STOT SE 2, H371 (10 =< C) STOT SE 1, H370	

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause an allergic skin reaction. May cause drowsiness or dizziness.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.
------------------	------------------------------------------------------------------------------------------------------------

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing vapors, mist, spray.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

UV resistant varnish satin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No naked lights. No smoking. Use only non-sparking tools. Avoid breathing vapors, mist, spray. Use only outdoors or in a well-ventilated area.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Explosion-free electrical equipment and lighting with earth.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure. Insufficient ventilation: wear respiratory protection. Gloves. Safety glasses.



Hand protection : Wear protective gloves. Since the product consists of several substances, it is possible to estimate the durability of the glove material beforehand and it therefore needs to be tested before use. Gloves must be replaced after each use and whenever signs of wear or perforation appear.

Eye protection : Chemical goggles or safety glasses.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Colourless.

Odour : characteristic.

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Self ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapour

UV resistant varnish satin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established. Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 4 mg/kg

methanol (67-56-1)

ATE (oral)	100,000 mg/kg bodyweight
ATE (dermal)	300,000 mg/kg bodyweight
ATE (gases)	700,000 ppmV/4h
ATE (vapours)	3,000 mg/l/4h
ATE (dust,mist)	0,500 mg/l/4h

Solventnaphta 170 (64742-95-6)

LD50 oral rat	3592 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
ATE (oral)	3592,000 mg/kg bodyweight

SILICA (7631-86-9)

LD50 oral rat	> 5110 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	0,139 mg/l/4h
ATE (dust,mist)	0,139 mg/l/4h

Skin corrosion/irritation	: Not classified Repeated exposure may cause skin dryness or cracking
Serious eye damage/irritation	: Not classified Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met

UV resistant varnish satin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Carcinogenicity	: Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Other information	: Risk of aspiration pneumonia.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)

EC50 Daphnia 1	7,8 g/l
EC50 other aquatic organisms 1	3,59 g/l

Solventnaphta 170 (64742-95-6)

LC50 fishes 1	9,2 mg/l
EC50 Daphnia 1	3,2 mg/l
ErC50 (algae)	2,6 - 2,9 mg/l
NOEC chronic fish	1,23 mg/l

SILICA (7631-86-9)

LC50 fishes 1	> 10000 mg/l
EC50 Daphnia 1	> 1000 mg/l
ErC50 (algae)	>= 10000 mg/l

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

LC50 fishes 1	2,8 mg/l
EC50 Daphnia 1	4 mg/l
ErC50 (algae)	> 9 mg/l

12.2. Persistence and degradability

UV resistant varnish satin

Persistence and degradability : May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

UV resistant varnish satin

Bioaccumulative potential : Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

: Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to an authorized waste treatment plant.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

UV resistant varnish satin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No (ADR) : 1263
UN-No.(IATA) : 1263
UN-No. (IMDG) : 1263
UN-No.(ADN) : 1263

14.2. UN proper shipping name

Proper Shipping Name : PAINT / PAINT RELATED MATERIAL
Transport document description : UN 1263 PAINT / PAINT RELATED MATERIAL, 3, III, (D/E)

14.3. Transport hazard class(es)

Class (UN) : 3
Classification code (UN) : F1
Class (IATA) : 3
Class (IMDG) : 3
Class (ADN) : 3
Hazard labels (UN) : 3



14.4. Packing group

Packing group (UN) : III

14.5. Environmental hazards

Dangerous for the environment : Yes
Marine pollutant : Yes



Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 30
Classification code (UN) : F1
Orange plates :



Special provision (ADR) : 163, 650, 640E
Transport category (ADR) : 3
Tunnel restriction code : D/E
Limited quantities (ADR) : 5L
Excepted quantities (ADR) : E1
EAC code : •3YE

14.6.2. Transport by sea

No additional information available

14.6.3. Air transport

No additional information available

14.6.4. Inland waterway transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

UV resistant varnish satin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

Contains no REACH candidate substance

Seveso Information :

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Abbreviations and acronyms : ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road). ATE: Acute Toxicity Estimated. CAS: Chemical Abstracts Service (division of the American Chemical Society). CLP: Classification, Labeling and Packaging. CMR: Carcinogen, Mutagen, Reprotoxisch. CSA: Chemical Safety Assessment. CSR: Chemical Safety Report. DNEL: Derived No Effect Level (for human). EC50: Median Effective Concentration (required to induce a 50% effect). EINECS: European Inventory of Existing Commercial Chemical Substances. GHS: Globally Harmonized System of Classification and Labelling of Chemicals. IATA: International Air Transport Association. IMDG: International Maritime Code for Dangerous Goods. LC50: Lethal concentration, 50 percent. LD50: Lethal dose, 50 percent. PBT: Persistent, Bio accumulating and Toxic. PNEC: Predicted No Effect Concentration (for environment). REACH: Registration, Evaluation and Authorisation of Chemical substances. RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail). SVHC: Substances of Very High Concern. vPvB: very Persistent, very Bio accumulating.

Other information : **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. **REACH Disclaimer:**
This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number).

Full text of R-, H- and EUH-phrases::

Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H317	May cause an allergic skin reaction

UV resistant varnish satin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

H330	Fatal if inhaled
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs
H411	Toxic to aquatic life with long lasting effects
R10	Flammable
R11	Highly flammable
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed
R37	Irritating to respiratory system
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed
R43	May cause sensitisation by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
T	Toxic
Xi	Irritant
Xn	Harmful

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product