

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5
Color'Résine
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation :** Adhesives
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Cléopâtre
12, bd de Chinon
37510 BALLAN
Téléphone: 0247801800
Fax: 0247801804
Email: info@colles-cleopatre.com
- **1.4 Emergency telephone number:**
France (INRS 24h/24) - Tel : +33 (0)1 45 42 59 59
Ireland - Tel : 00 353 1 8092568 - 00 353 1 8379964 (24h/24) EU Tel: 112
Belgique - Tel : 32 070/245 245
UK : +44 (0)-870-190-6777 (CARECHEM24)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008 :**



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
1-methoxy-2-propanol
acetone

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 1)

- **Hazard statements**
 - H225 Highly flammable liquid and vapour.
 - H319 Causes serious eye irritation.
 - H336 May cause drowsiness or dizziness.
- **Precautionary statements**
 - P102 Keep out of reach of children.
 - P241 Use explosion-proof electrical/ventilating/lighting equipment.
 - P243 Take precautionary measures against static discharge.
 - P233 Keep container tightly closed.
 - P261 Avoid breathing vapours.
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P264 Wash hands thoroughly after handling.
- **Additional information:**
 - EUH066 Repeated exposure may cause skin dryness or cracking.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 RTECS: UB 7700000 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25-50%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 RTECS: KQ 6300000 Reg.nr.: 01-2119457610-43-xxxx	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49-XXXX	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; ⚠ STOT SE 3, H336	10-25%
CAS: 108-94-1 EINECS: 203-631-1 Index number: 606-010-00-7 RTECS: GW 1050000 Reg.nr.: 01-2119453616-35-XXXX	cyclohexanone ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332	5-10%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 2)

CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 RTECS: DN 3150000 Reg.nr.: 01-2119492630-38-XXXX	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	5-10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 RTECS: EO 1400000 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	<5%
CAS: 123-42-2 EINECS: 204-626-7 RTECS: SA 9100000 Reg.nr.: 01-2119473975-21	diacetone alcohol, technical ⚠ Eye Irrit. 2, H319	<5%
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X RTECS: PC 1400000 Reg.nr.: 01-2119433307-44	methanol ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT SE 1, H370	<1%

- SVHC No

- **Additional information:** For the wording of the listed risk phrases, refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **After excessive inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient in a stable laying down side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** Do not induce vomiting; call for medical help immediately.

- **4.2 Most important symptoms and effects, both acute and delayed :**

No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed :**

No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **5.2 Special hazards arising from the substance or mixture :**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- **5.3 Advice for firefighters**

- **Protective equipment:** Mouth respiratory protective device.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 3)

· **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures :**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Dilute with plenty of water.
Do not allow the product to enter sewers/ surface water or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections :**
See Section 7 for information on safe handling.
See Section 8 for information on personal protective equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling :**
Keep receptacles tightly sealed.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

- Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s) :** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 4)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol (25-50%)

WEL (Great Britain)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
IOELV (EU)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Skin
MAK (Switzerland)	Short-term value: 720 mg/m ³ , 200 ppm Long-term value: 360 mg/m ³ , 100 ppm B SSc;

64-17-5 ethanol (10-25%)

WEL (Great Britain)	Long-term value: 1920 mg/m ³ , 1000 ppm
MAK (Switzerland)	Short-term value: 1920 mg/m ³ , 1000 ppm Long-term value: 960 mg/m ³ , 500 ppm SSc;

67-64-1 acetone (10-25%)

WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm
MAK (Switzerland)	Short-term value: 2400 mg/m ³ , 1000 ppm Long-term value: 1200 mg/m ³ , 500 ppm B;

108-94-1 cyclohexanone (5-10%)

WEL (Great Britain)	Short-term value: 82 mg/m ³ , 20 ppm Long-term value: 41 mg/m ³ , 10 ppm Sk, BMGV
IOELV (EU)	Short-term value: 81.6 mg/m ³ , 20 ppm Long-term value: 40.8 mg/m ³ , 10 ppm Skin
MAK (Switzerland)	Short-term value: 200 mg/m ³ , 50 ppm Long-term value: 100 mg/m ³ , 25 ppm H B SSc;

71-36-3 butan-1-ol (<5%)

WEL (Great Britain)	Short-term value: 154 mg/m ³ , 50 ppm Sk
MAK (Switzerland)	Short-term value: 150 mg/m ³ , 50 ppm Long-term value: 150 mg/m ³ , 50 ppm SSc;

123-42-2 diacetone alcohol, technical (<5%)

WEL (Great Britain)	Short-term value: 362 mg/m ³ , 75 ppm Long-term value: 241 mg/m ³ , 50 ppm
MAK (Switzerland)	Short-term value: 192 mg/m ³ , 40 ppm Long-term value: 96 mg/m ³ , 20 ppm H;

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 5)

67-56-1 methanol (<1%)

WEL (Great Britain)	Short-term value: 333 mg/m ³ , 250 ppm Long-term value: 266 mg/m ³ , 200 ppm Sk
IOELV (EU)	Long-term value: 260 mg/m ³ , 200 ppm Skin
MAK (Switzerland)	Short-term value: 1040 mg/m ³ , 800 ppm Long-term value: 260 mg/m ³ , 200 ppm H B SSc;

67-63-0 propan-2-ol (<1%)

WEL (Great Britain)	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
MAK (Switzerland)	Short-term value: 1000 mg/m ³ , 400 ppm Long-term value: 500 mg/m ³ , 200 ppm B SSc;

· Ingredients with biological limit values:

107-98-2 1-methoxy-2-propanol (25-50%)

BAT (Switzerland)	20 mg/l Medium: U Sampling time: b Parameter: 1-Methoxypropanol-2
-------------------	--

67-64-1 acetone (10-25%)

BAT (Switzerland)	80 mg/l Medium: U Sampling time: b Parameter: Aceton
-------------------	---

108-94-1 cyclohexanone (5-10%)

BMGV (Great Britain)	2 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: cyclohexanol
BAT (Switzerland)	100 mg/l Medium: U Sampling time: b,c Parameter: Gesamt-1.2-Cyclohexandiol
	12 mg/l Medium: U Sampling time: b,c Parameter: Gesamt-Cyclohexanol

67-56-1 methanol (<1%)

BAT (Switzerland)	30 mg/l Medium: U Sampling time: c,b Parameter: Methanol
-------------------	---

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 6)

67-63-0 propan-2-ol (<1%)

BAT (Switzerland)	25 mg/l
	Medium: U Sampling time: b Parameter: Aceton

	25 mg/l
	Medium: B Sampling time: b Parameter: Aceton

· **Additional information:**

The most current valid lists have been used as a basis for the production of this document.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from food, beverages and petfood.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid all contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

· **Gloves material : Butyl rubber, BR**

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 7)

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid
Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: -95 °C

Initial boiling point and boiling range: 60 °C

· **Flash point:** -9 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 270 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not self igniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 2.3 Vol %

Upper: 20.0 Vol %

· **Vapour pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** ~0.885 g/cm³

· **Relative density :** Not determined.

· **Vapour density :** Not determined.

· **Evaporation rate :** Not determined.

· **Solubility in / Miscibility with water:**

Fully miscible.

· **Segregation coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

· **Solvent content:**

COV : 95.0 %

· **9.2 Other information :** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions :** No dangerous reactions known.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 8)

- **10.4 Conditions to avoid** : No further relevant information available.
- **10.5 Incompatible materials**: No further relevant information available.
- **10.6 Hazardous decomposition products**: No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

107-98-2 1-methoxy-2-propanol

Oral	LD50	5660 mg/kg (rat)
Dermal	LD50	13000 mg/kg (rabbit)

64-17-5 ethanol

Oral	LD50	7060 mg/kg (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

108-94-1 cyclohexanone

Oral	LD50	1535 mg/kg (rat)
Dermal	LD50	948 mg/kg (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

71-36-3 butan-1-ol

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3400 mg/kg (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

123-42-2 diacetone alcohol, technical

Oral	LD50	4000 mg/kg (rat)
Dermal	LD50	13630 mg/kg (rab)

67-56-1 methanol

Oral	LD50	5628 mg/kg (rat)
Dermal	LD50	15800 mg/kg (rabbit)
Inhalative	LC50/4 h	3 mg/l (ATE)

- **Primary irritant effect:**
- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eyes:**
Causes serious eye irritation.
- **Respiratory or skin sensitization** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 9)

- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

71-36-3 butan-1-ol

EC50	1730 mg/kg (fish)
LC50 48h	1983 mg/l (daphnia)

- **12.2 Persistence and degradability** : No further relevant information available.
- **12.3 Bioaccumulative potential** : No further relevant information available.
- **12.4 Mobility in soil** : No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT**: Not applicable.
- **vPvB**: Not applicable.
- **12.6 Other adverse effects** : No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation :**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1263

· **14.2 UN proper shipping name**

· **ADR** UN1263 PAINT, special provision 640D
· **IMDG, IATA** PAINT

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 10)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 3 (F1) Flammable liquids.
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user**

Warning: Flammable liquids.
· **Danger code (Kemler):** 33
· **EMS Number:** F-E,S-E
· **Stowage Category** B

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 5L
· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
· **Transport category** 2
· **Tunnel restriction code** D/E

· **IMDG**

· **Limited quantities (LQ)** 5L
· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I methanol**

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.02.2017

Version number 1

Revision: 22.02.2017

Trade name: COL15-12 - COL15-16 - COL15-2 - COL15-8 - COL15-15 - COL15-18 - COL15-5 Color'Résine

(Contd. of page 11)

- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t**
- **Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t**
- **REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3**
- **15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3