

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 310 - AEROPUMP fixative for charcoal/pencil

Article No. Issue date: 16.04.18
Version 6 (16.04.18) Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name 50 310 - AEROPUMP fixative for charcoal/pencil

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use
Products for creation of art.

Uses advised against

1.3 Details of the supplier of the safety data sheet

H. Schmincke & Co. GmbH & Co. KG
Otto-Hahn-Str. 2
D - 40699 Erkrath
Tel. +49 (0) 211-2509-0
Fax. +49 (0) 211-2509-497
info@schmincke.de
www.schmincke.de

Dept. responsible for information
Schmincke-lab:
mo-th 8.00-16.30, fr 8.00-13.30
Tel. +49 (0) 211-2509-474
labor@schmincke.de

1.4 Emergency telephone number

Emergency
Information
Phone #

Emergencycall Berlin
(24h - counseling in german and english)
+49 (0) 30-30686700

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Eye Irrit. 2; H319 Causes serious eye irritation.
Flam. Liq. 2; H225 Highly flammable liquid and vapour.

2.2 Label elements

Labelling (CLP)



Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

Safety precautions

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe spray.
P271 Use only outdoors or in a well-ventilated area.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 310 - AEROPUMP fixative for charcoal/pencil

Article No.		Issue date:	16.04.18
Version	6 (16.04.18)	Page	2 / 9

lenses, if present and easy to do. Continue rinsing.

2.3 Other hazards

SECTION 3: Composition / information on ingredients

3.1 Substances

Chemical characterisation

Alcohol
shellac
ketone resin

CAS-Number
EINECS / ELINCS / NLP
EU index number
Customs tariff number
REACH registration No.
RTECS-no.
Hazchem-Code
CI-Number

3.2 Mixtures

Substance 1

ethanol: 70 - 90 %
CAS: 64-17-5
REACH: 01-2119457610-43-XXXX
Eye Irrit. 2; H319 / Flam. Liq. 2; H225

Substance 2

butan-1-ol: 1,0 - 2,0 %
CAS: 71-36-3
REACH: 01-2119484630-38-xxxx
Acute Tox. 4; H302 / Acute Tox. 4; H332 / Eye Dam. 1;
H318 / Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE
3; H336 / Skin Irrit. 2; H315

Additional information

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If you feel unwell, seek medical advice (show the label where possible).

In case of inhalation

Provide fresh air. Seek medical attention if problems persist.

In case of skin contact

Remove residues with soap and water. In case of skin irritation, consult a physician.

After eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing

Rinse mouth with water. Seek medical treatment in case of troubles.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 310 - AEROPUMP fixative for charcoal/pencil

Article No. Issue date: 16.04.18
Version 6 (16.04.18) Page 3 / 9

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons
strong water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters
Use appropriate respiratory protection.

Additional information

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes, and clothing.

6.2 environmental precautions

Discharge into the environment must be avoided.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Collect spilled material using paper towels and dispose. Provide adequate ventilation.

Additional information

6.4 Reference to other sections

Dispose of waste according to applicable legislation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Precautions against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers

Keep in a cool, well-ventilated place.

Hints on joint storage

Storage class

Further details

Protect from frost and exposure to sun.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

64-17-5 ethanol

DEU	WEL	500,000	mL/m ³	-
DEU	WEL	960,000	mg/m ³	2(II); DGF; Y
USA	PEL (US)	1.000,000	ppm	8h (long term)
USA	PEL (US)	1.900,000	mg/m ³	8h (long term)

71-36-3 butan-1-ol

DEU	WEL	100,000	mL/m ³	1(I); DFG, Y
DEU	WEL	310,000	mg/m ³	1(I); DFG, Y

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 310 - AEROPUMP fixative for charcoal/pencil

Article No.		Issue date:	16.04.18
Version	6 (16.04.18)	Page	4 / 9

8.2 Exposure controls

Occupational exposure controls

Respiratory protection

Respiratory protection must be worn whenever the WEL levels have been exceeded.
Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

Hand protection

Qualified materials: Butyl caoutchouc (butyl rubber)

Layer thickness > 0,5 mm

Breakthrough time > 480 min

Butoflex 650 - MAPA GmbH, Industriestraße 21- 25, D-27404 Zeven, Internet: www.mapa-pro.de

All information was derived in accordance with EU directive 89/686/EEG and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves.

Eye protection

Goggles

Body protection

Wear suitable protective clothing.

General protection and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands thoroughly after handling.

SECTION 9: Physical and chemical properties

9.1 information on basic physical and chemical properties

Form	liquid
Colour	colourless
Odour	alcoholic

	min	max
Initial boiling point and boiling range		
Melting point/freezing point		
Flash point/flash point range	12 °C	
Flammability		
Ignition temperature	363 °C	
Auto-ignition temperature		
Explosion limits	3,3	19 %
Refraction index		

Partition coefficient: n-octanol/water

Danger of explosion

Vapour pressure	5,9 kPa	20 °C
Density	0,86 g/ml	20 °C
PH value		

Viscosity dynamic of

Viscosity dynamic up to

Viscosity kinematic of

Viscosity kinematic up to

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

Product is stable under normal storage conditions.

10.2 Chemical stability

10.3 Possibility of hazardous reactions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 310 - AEROPUMP fixative for charcoal/pencil

Article No.
Version

6 (16.04.18)

Issue date: 16.04.18
Page 5 / 9

10.4 Conditions to avoid

Protect from frost and exposure to sun.

10.5 Incompatible materials

10.6 Hazardous decomposition products

Hazardous vapours may form during fires.

64-17-5

ethanol

oral	LD50	Rat		5000,000	mg/kg	-
inhalative	LC50	Rat	>	1800,000	mg/l	4h
dermal	LD50	Rabbit	>	10000,000	mg/kg	-

71-36-3

butan-1-ol

oral	LD50	Rat		1000,000	mg/kg	-
inhalative	LC50	Rat	>	17,760	mg/l	(4h)
dermal	LD50	Rabbit	>	2000,000	mg/kg	-

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

In case of inhalation

After swallowing

In case of skin contact

After eye contact

Practical experience

General remarks

Toxicological tests

64-17-5

ethanol

LC50	fish			8150,000	mg/l	48h
EC50	Daphnia magna	>		14221,000	mg/l	48h

71-36-3

butan-1-ol

EC50	Daphnia magna (Big water)			1328,000	mg/l	(48h)
IC50:	Algae	>		500,000	mg/l	(72h)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Water Hazard Class

1

WGK catalog number

General information

12.2 Persistence and degradability

Further details

Product is partially biodegradable.

Oxygen demand

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)

Partition coefficient: n-octanol/water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 310 - AEROPUMP fixative for charcoal/pencil

Article No.		Issue date:	16.04.18
Version	6 (16.04.18)	Page	6 / 9

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information

Ecotoxicological effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number

080111

Waste paint and varnish containing organic solvents or other dangerous substances

Recommendation

Contaminated packaging

Waste key number

Recommendation

Non-contaminated packages may be recycled.

Additional information

SECTION 14: Transport information

14.1 UN number

1263

14.2 UN proper shipping name

ADR, ADN Paint related material

IMDG, IATA PAINT or PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR, ADN 3

IMDG 3

IATA 3

14.4 Packing group

II

14.5 Environmental hazards

Marine Pollutant - IMDG No

Marine Pollutant - ADN

14.6 Special precautions for user

Land transport

Code: ADR/RID F1

Kemmler-number 33

Hazard label ADR 3

Limited quantities 5L

Contaminated packaging: Instructions P001 - IBC02 - R001

Contaminated packaging: Special provisions PP1

Special provisions for packing together MP19

Portable tanks: Instructions T4

Portable tanks: Special provisions TP1 - TP8 - TP28

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 310 - AEROPUMP fixative for charcoal/pencil

Article No.		Issue date:	16.04.18
Version	6 (16.04.18)	Page	7 / 9

Tank coding	LGBF
Tunnel restriction	D/E
Remarks	
EQ	E2
Special provisions	163 - 367 - 640D - 650

Inland waterway craft

Hazard label	
Limited quantities	
Transport permitted	
Equipment necessary	
Ventilation	
Remarks	
EQ	
Special provisions	

Sea transport

EmS	F-E, S-E
Special provisions	163 - 367
Limited quantities	5L
Contaminated packaging: Instructions	P001
Contaminated packaging: Special provisions	PP1
IBC: Instructions	IBC02
IBC: Provisions	-
Tank instructions IMO	-
Tank instructions UN	T4
Tank instructions Special provisions	TP1 - TP8 - TP28
Stowage and segregation	category B
Properties and observations	
Remarks	
EQ	E2

Air transport

Hazard	Flammable Liquid
Passenger	353 (5L)
Passenger LQ	Y341 (1L)
Cargo	364 (60L)
ERG	3L
Remarks	
EQ	E2
Special Provisioning	A72

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Europe

Contents of VOC [%]
Contents of VOC
[g/L]
Further regulations, limitations and legal requirements

Germany

Storage class

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 310 - AEROPUMP fixative for charcoal/pencil

Article No.		Issue date:	16.04.18
Version	6 (16.04.18)	Page	8 / 9

Water Hazard Class 1
WGK catalog number
Incident regulation
Information on working limitations
Further regulations, limitations and legal requirements

Denmark

Further regulations, limitations and legal requirements

Hungary

Further regulations, limitations and legal requirements

Great Britain

Further regulations, limitations and legal requirements

Switzerland

Contents of VOC [%]
~ 90 %
Further regulations, limitations and legal requirements

USA

Further regulations, limitations and legal requirements
Federal Regulations
State Regulations

Japan

Further regulations, limitations and legal requirements

Canada

Further regulations, limitations and legal requirements

15.2 Chemical Safety Assessment

SECTION 16: Other information

Further information

Hazard statements (CLP)	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
--------------------------------	--

Further information

This information is based on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

Literature

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Reason of change

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 310 - AEROPUMP fixative for charcoal/pencil

Article No.		Issue date:	16.04.18
Version	6 (16.04.18)	Page	9 / 9

Additional information