

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY films (varnishes), mineral spirit containing

Article No. Issue date: 16.04.18
Version 8 (16.04.18) Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name 50 408 - AEROSPRAY matt film (varnish)
50 410 - AEROSPRAY neutral film (varnish)
50 412 - AEROSPRAY gloss film (varnish)

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use

Products for creation of art.

Uses advised against

1.3 Details of the supplier of the safety data sheet

H. Schmincke & Co. GmbH & Co. KG
Otto-Hahn-Str. 2
D - 40699 Erkrath
Tel. +49 (0) 211-2509-0
Fax. +49 (0) 211-2509-497
info@schmincke.de
www.schmincke.de

Dept. responsible for information

Schmincke-lab:
mo-th 8.00-16.30, fr 8.00-13.30
Tel. +49 (0) 211-2509-474
labor@schmincke.de

1.4 Emergency telephone number

**Emergency
Information
Phone #**

**Emergencycall Berlin
(24h - counseling in german and english)
+49 (0) 30-30686700**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aquatic Chronic 2; H411 Toxic to aquatic life with long lasting effects.
Eye Irrit. 2; H319 Causes serious eye irritation.
Flam. Aerosol 1; H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
STOT RE 2; H373 May cause damage to organs through prolonged or repeated exposure.
STOT SE 3; H335 May cause respiratory irritation.
STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling (CLP)



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	16.04.18
Version	8 (16.04.18)	Page	2 / 10

H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Safety precautions

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P271 Use only outdoors or in a well-ventilated area.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER if you feel unwell.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

2.3 Other hazards

Repeated exposure may cause skin dryness or cracking. (EUH066)
Contains benzotriazole derivate, alkylmethacrylate. May produce an allergic reaction. (EUH208)

SECTION 3: Composition / information on ingredients

3.1 Substances

Chemical characterisation

acrylic resin
white spirit
Alcohols
matting agents (50 408 / 50 410)
propellant (propane / butane)
CAS-Number
EINECS / ELINCS / NLP
EU index number
Customs tariff number
REACH registration No.
RTECS-no.
Hazchem-Code
CI-Number

3.2 Mixtures

Substance 1

solvent naphtha (petroleum), light, aromatic: 25 - 50 %
CAS: 64742-95-6
REACH: 01-2119455851-35
Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE 3; H336 / EUH066

Substance 3

naphtha (petroleum), hydrotreated light: 0 - < 10 %
CAS: 64742-49-0
Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / Flam. Liq. 2; H225 / STOT SE 3; H336 / EUH066

Substance 2

naphtha (petroleum), hydrodesulphurized heavy: 3 - < 10 %
CAS: 64742-82-1
REACH: 01-2119458049-33-xxxx
Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / Flam. Liq. 3; H226 / STOT RE 1; H372 / STOT SE 3; H336 / EUH066

Substance 4

butan-1-ol: 1,0 - < 3,0 %
CAS: 71-36-3
REACH: 01-2119484630-38-xxxx
Acute Tox. 4; H302 / Acute Tox. 4; H332 / Eye Dam. 1;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY films (varnishes), mineral spirit containing

Article No. 8 (16.04.18) Issue date: 16.04.18
Version 8 (16.04.18) Page 3 / 10

H318 / Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE 3; H336 / Skin Irrit. 2; H315

Substance 5

ethanol: 0 - < 2 %
CAS: 64-17-5
REACH: 01-2119457610-43-XXXX
Eye Irrit. 2; H319 / Flam. Liq. 2; H225

Substance 6

derivate of Benzotriazol: 0,1 - < 1,0 %
CAS: 104810-47-1
Aquatic Chronic 2; H411 / Skin Sens. 1; H317

Substance 7

alkylmethacrylate: 0,1 - < 1,0 %
CAS: 97-88-1
Eye Irrit. 2; H319 / Flam. Liq. 3; H226 / STOT SE 3;
H335 / Skin Irrit. 2; H315 / Skin Sens. 1; H317

Substance 8

butane: 20 - 30 %
CAS: 106-97-8
REACH: 01-2119474691-32
Compr. Gas; H280 / Flam. Gas 1; H220

Substance 9

propane: 1 - 10 %
CAS: 74-98-6
REACH: 01-2119471330-49
Compr. Gas; H280 / Flam. Gas 1; H220

Additional information

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of inhalation

Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical attention if problems persist.

In case of skin contact

Thoroughly wash skin with soap and water. Seek medical attention if irritation persists.

After eye contact

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After swallowing

Call a POISON CENTER/doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

extinguishing powder carbon dioxide Water fog

Extinguishing media which must not be used for safety reasons

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters

Use appropriate respiratory protection.

Additional information

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY films (varnishes), mineral spirit containing

Article No. **8 (16.04.18)** Issue date: **16.04.18**
Version **8 (16.04.18)** Page **4 / 10**

refer to section 8

6.2 environmental precautions

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Absorb leftover product with non-flammable liquid-binding material (e.g. earth, sand, vermiculite or ground sand stone) and place in closed containers for disposal.

Additional information

6.4 Reference to other sections

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Provide good ventilation and/or an exhaust system in the work area. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Precautions against fire and explosion

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers

Store in a well-ventilated place. Keep container tightly closed. Keep away from sources of ignition and heat. Protect from direct sunlight.

Hints on joint storage

Storage class

Further details

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

64742-95-6 solvent naphtha (petroleum), light, aromatic

DEU	WEL	50,000	mg/m ³	TRGS 900
-----	-----	--------	-------------------	----------

71-36-3 butan-1-ol

DEU	WEL	100,000	mL/m ³	1(I); DFG, Y
DEU	WEL	310,000	mg/m ³	1(I); DFG, Y

64-17-5 ethanol

DEU	WEL	500,000	mL/m ³	-
DEU	WEL	960,000	mg/m ³	2(II); DGF; Y
USA	PEL (US)	1,000,000	ppm	8h (long term)
USA	PEL (US)	1,900,000	mg/m ³	8h (long term)

106-97-8 butane

DEU	WEL	1,000,000	mL/m ³	-
DEU	WEL	2,400,000	mg/m ³	4(II); DGF

74-98-6 propane

DEU	WEL	1,000,000	mL/m ³	-
DEU	WEL	1,800,000	mg/m ³	4(II); DFG

8.2 Exposure controls

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	16.04.18
Version	8 (16.04.18)	Page	5 / 10

Occupational exposure controls

Respiratory protection

Respiratory protection must be worn whenever the WEL levels have been exceeded.
Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

Hand protection

Qualified materials: Nitrile rubber
Layer thickness > 0,35 mm
Breakthrough time > 480 min
Ultranitril 492 - MAPA GmbH, Industriestraße 21- 25, D-27404 Zeven, Internet: www.mapa-pro.de
All information was derived in accordance with EU directive 89/686/EWG and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves.
This information is based on our current state of knowledge and describes the security standards applicable to our product for the purpose provided.

Eye protection

Goggles

Body protection

Wash contaminated clothing prior to re-use.

General protection and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. After work, wash hands and face.

SECTION 9: Physical and chemical properties

9.1 information on basic physical and chemical properties

Form	Aerosol
Colour	colourless
Odour	characteristic

	min	max
Initial boiling point and boiling range		
Melting point/freezing point		
Flash point/flash point range	-60 °C	-60 °C
Flammability		
Ignition temperature		
Auto-ignition temperature		
Explosion limits	0,6	8,5 Vol%
Refraction index		

Partition coefficient: n-octanol/water

Danger of explosion

Vapour pressure	300 kPa
Density	~ 0,71 g/ml

PH value

Viscosity dynamic of

Viscosity dynamic up to

Viscosity kinematic of

Viscosity kinematic up to

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY films (varnishes), mineral spirit containing

Article No. **8 (16.04.18)** Issue date: **16.04.18**
Version **8 (16.04.18)** Page **6 / 10**

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Protect from heat and direct sunlight.

10.5 Incompatible materials

Oxidising agent

10.6 Hazardous decomposition products

64742-95-6 solvent naphtha (petroleum), light, aromatic

oral	LD50	Rat	>	2000,000	mg/kg	-
dermal	LD50	Rat	>	2000,000	mg/kg	-

64742-82-1 naphtha (petroleum), hydrodesulphurized heavy

oral	LD50	Rat	>	2000,000	mg/kg	-
dermal	LD50	Rat	>	2000,000	mg/kg	-

71-36-3 butan-1-ol

oral	LD50	Rat		1000,000	mg/kg	-
inhalative	LC50	Rat	>	17,760	mg/l	(4h)
dermal	LD50	Rabbit	>	2000,000	mg/kg	-

64-17-5 ethanol

oral	LD50	Rat		5000,000	mg/kg	-
inhalative	LC50	Rat	>	1800,000	mg/l	4h
dermal	LD50	Rabbit	>	10000,000	mg/kg	-

97-88-1 alkylmethacrylate

oral	LD50	Rat		16000,000	mg/kg	-
dermal	LD50	Rabbit	>	10100,000	mg/kg	-

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

In case of inhalation

May cause respiratory irritation.

After swallowing

No data available

In case of skin contact

No data available

After eye contact

Causes serious eye irritation.

Practical experience

General remarks

Toxicological tests

64742-95-6 solvent naphtha (petroleum), light, aromatic

LC50	fish	>	10,000	mg/l	-
LC50	Algae	>	10,000	mg/l	-

64742-82-1 naphtha (petroleum), hydrodesulphurized heavy

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY films (varnishes), mineral spirit containing

Article No. **8 (16.04.18)** Issue date: **16.04.18**
Version **8 (16.04.18)** Page **7 / 10**

71-36-3	butan-1-ol	LC50	fish	>	10,000	mg/l	-
		EC50	Algae	>	10,000	mg/l	-
64-17-5	ethanol	EC50	Daphnia magna (Big water		1328,000	mg/l	(48h)
		IC50:	Algae	>	500,000	mg/l	(72h)
		LC50	fish		8150,000	mg/l	48h
		EC50	Daphnia magna	>	14221,000	mg/l	48h

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Water Hazard Class

2

WGK catalog number

General information

12.2 Persistence and degradability

Further details

Oxygen demand

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)

Partition coefficient: n-octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information

Ecotoxicological effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number

160504

Gases in pressure containers (including halons) containing hazardous substances

Recommendation

Contaminated packaging

Waste key number

Recommendation

Completely emptied packages can be recycled.

Additional information

SECTION 14: Transport information

14.1 UN number

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY films (varnishes), mineral spirit containing

Article No. 1950 Issue date: 16.04.18
Version 8 (16.04.18) Page 8 / 10

1950

14.2 UN proper shipping name

ADR, ADN AEROSOLS, flammable
IMDG, IATA AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR, ADN 2
IMDG 2.1
IATA 2.1

14.4 Packing group

-

14.5 Environmental hazards

Marine Pollutant - IMDG Yes
Marine Pollutant - ADN

14.6 Special precautions for user

Land transport

Code: ADR/RID 5F
Kemmler-number -
Hazard label ADR 2.1
Limited quantities 1L
Contaminated packaging: Instructions P207 - LP200
Contaminated packaging: Special provisions PP87 - RR6 - L2
Special provisions for packing together MP9
Portable tanks: Instructions -
Portable tanks: Special provisions -
Tank coding -
Tunnel restriction D
Remarks
EQ E0
Special provisions 190 - 327 - 344 - 625

Inland waterway craft

Hazard label
Limited quantities
Transport permitted
Equipment necessary
Ventilation
Remarks
EQ
Special provisions

Sea transport

EmS F-D, S-U
Special provisions 63 - 190 - 277 - 327 - 344 - 381 - 959
Limited quantities 1L
Contaminated packaging: Instructions P207 - LP200
Contaminated packaging: Special provisions PP87 - L2
IBC: Instructions -
IBC: Provisions -
Tank instructions IMO -
Tank instructions UN -
Tank instructions Special provisions -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	16.04.18
Version	8 (16.04.18)	Page	9 / 10

Stowage and segregation category A
SW1 - SG69

Properties and observations

Remarks

EQ E0

Air transport

Hazard -
Passenger 203 (75 kg)
Passenger LQ Y203 (30 kg G)
Cargo 203 (150 kg)
ERG 10L
Remarks
EQ
Special Provisioning A145 - A167 - A802

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Europe

Contents of VOC [%] 0
Contents of VOC
[g/L]
Further regulations, limitations and legal requirements

Germany

Storage class
Water Hazard Class 2
WGK catalog number
Incident regulation
Information on working limitations
Further regulations, limitations and legal requirements

Denmark

Further regulations, limitations and legal requirements

Hungary

Further regulations, limitations and legal requirements

Great Britain

Further regulations, limitations and legal requirements

Switzerland

Contents of VOC [%]
~ 87 %
Further regulations, limitations and legal requirements

USA

Further regulations, limitations and legal requirements
Federal Regulations

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	16.04.18
Version	8 (16.04.18)	Page	10 / 10

State Regulations

Japan

Further regulations, limitations and legal requirements

Canada

Further regulations, limitations and legal requirements

15.2 Chemical Safety Assessment

SECTION 16: Other information

Further information

Hazard statements (CLP)	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: May burst if heated. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
--------------------------------	---

Further information

This information is based on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

Literature

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Reason of change

Additional information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.